NIGHT STICK®
Life Depends on Light™

Intrinsically Safe Polymer Penlights

These non-rechargeable penlights are cETLus, ATEX and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present. They are ultra-compact and super slim with a powerful light output designed to illuminate very tight spaces. The tail-cap switch provides momentary or constant-on functionality. Power comes from 2 AAA (5410) & 3 AAAA (5412) premium batteries (included).

INTRINSICALLY SAFE

XPP-5410G

XPP-5412G

30 or 50 Lumens

- cETLus, ATEX and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present.
- **Engineered polymer housing**
- **Powered by AAA/AAAA batteries**

WATER PROOF

XPP 5410 series

NIGHT STICK®
Life Depends on Light™

XPP 5410 series



High-efficiency deep parabolic reflector

Intrinsically Safe Polymer Penlights

XPP-5412G

XPP-5410G

FEATURES

- CREE® LED technology – 50,000 + hours LED life
- Momentary or constant-on flashlight
- Sharp focused beam for distance illumination
- Engineered polymer housing
- Single tail switch
- Waterproof
- Impact & chemical resistant
- Built-in pocket/belt clip
- Powered by 2 AAA batteries (5410) & 3 AAAA batteries (5412) included
- Limited Lifetime Warranty*

XPP-5410G

XPP-5412G



High-efficiency deep parabolic reflector

Push-button tail-cap switch

CLASS I DIV 1 GRPS A-D T3
CLASS II & III DIV I GRPS E-G T135C
CLASS I ZONE 0 AEx ia IIC T3 Ga
CLASS I ZONE 0 Ex ia IIC T3 Ga
Ex I M1 Ex ia I Ma
Ex II 1 G Ex ia IIC T3 Ga
Ex ia I Ma
Ex ia IIC T3 Ga
Intertek ITS 13 ATEX27839X
IECEx ETL 13.0024X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell AAA Alkaline
CE 0359

c ETL us
ID 4001184
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

Conforms to:
ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11
Certified to:
CAN/CSA STD C22.2 NO 157
CAN/CSA STD C22.2 No 60079-0
CAN/CSA STD C22.2 No 60079-11
CSA STD C22.2 No 25

CLASS I DIV 1 GRPS A-D T3
CLASS II & III DIV I GRPS E-G T135C
CLASS I ZONE 0 AEx ia IIC T3 Ga
CLASS I ZONE 0 Ex ia IIC T3 Ga
Ex I M1 Ex ia I Ma
Ex II 1 G Ex ia IIC T3 Ga
Ex ia I Ma
Ex ia IIC T3 Ga
Intertek ITS 13 ATEX27839X
IECEx ETL 13.0024X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell AAAA Alkaline
CE 0359

c ETL us
ID 4001184
INTRINSICALLY SAFE
SECURITE INTRINSEQUE

Conforms to:
ANSI/UL STD 913, ANSI/UL 60079-0, ANSI/UL 60079-11
Certified to:
CAN/CSA STD C22.2 NO 157
CAN/CSA STD C22.2 No 60079-0
CAN/CSA STD C22.2 No 60079-11
CSA STD C22.2 No 25

XPP-5410G SPECIFICATIONS

- Lumens: 30
- Run-time: 18 hrs
- Beam distance: 40 meters
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Length: 5.8in, head diameter: 0.9in, handle diameter: 0.7in, weight: 1.9oz



XPP-5412G SPECIFICATIONS

- Lumens: 50
- Lumens: 50
- Run-time: 13.75 hrs
- Beam distance: 50 meters
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Length: 6.8in, head diameter: 0.6in, handle diameter: 0.5in, weight: 1.5oz



INCLUDED

XPP-5410G
- Flashlight
- 2 AAA premium alkaline batteries

XPP-5412G
- Flashlight
- 3 AAAA premium alkaline batteries

SAFETY RATING

cETLus, ATEX and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present.

Patent 7,738,229

Model	UPC 0 17398
XPP-5410G	80298 7
XPP-5412G	80299 4

*Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the lifetime of the original owner. Includes the LEDs, housing, lenses, electronics and switches. Batteries, normal wear and abuse are excluded.