NIGHT STICK®
Life Depends on Light™

Intrinsically Safe Polymer Dual-Light

Flashlight

Floodlight

Dual-Light

These non-rechargeable dual-lights are cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible for use in both above and below ground hazardous locations where explosive gases and dusts may be present. They each use a CREE® LED rated at 120 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 170 meters. A 120 lumens unfocused floodlight is integrated into the housing which is perfect for close-up illumination. Additionally both the flashlight and the floodlight can be turned on at the same time for maximum versatility. The dual body switches provide momentary or constant-on functionality for the flashlight and on/off functionality for the floodlight. Power comes from 3 AA batteries (not included).

INTRINSICALLY SAFE

XPP-5422G

120 *Flashlight Lumens*

120 *Floodlight Lumens*

- cETLus, ATEX, IECEx and MSHA listed **Intrinsically** Safe Permissible for use in both **above and below** ground hazardous locations where **explosive** gases and dusts may be present.
- **Flashlight/floodlight/dual-light**
- **Beam distance rated at 170 meters**
- **Engineered polymer housing**

WATER PROOF

XPP-5422B

XPP 5420 series

NIGHTSTICK®
Life Depends on Light™

XPP 5420 series

High-efficiency deep parabolic reflector

Intrinsically Safe Polymer Dual-Light

XPP-5422G

XPP-5422B

FEATURES

- Flashlight – floodlight – dual-light
- CREE® LED technology – 50,000 + hours LED life
- Momentary or constant-on flashlight
- Sharp focused beam for distance illumination
- Unfocused wide-beam floodlight for close-up illumination
- Dual-light (flashlight & floodlight at same time) for maximum versatility
- Engineered polymer housing
- Non-slip grip
- Dual body switches
- Waterproof
- Impact & chemical resistant
- Built-in pocket/belt clip
- Includes removable lanyard
- Requires 3 AA batteries (not included)
- Available in black & green
- Limited Lifetime Warranty*

SPECIFICATIONS

- Lumens: flashlight-120, floodlight-120, dual-light-240
- Run-time: flashlight-17.5 hrs, floodlight-17.5 hrs, dual-light-4.5 hrs
- Beam distance: 170 meters
- Water rating: IP-X7 waterproof
- Drop rating: 2 meters
- Length: 7in, head diameter: 1.8in, handle diameter: 1.5 x 1.1in, weight: 6.9oz



INCLUDED

- Flashlight with built-in pocket/belt clip
- Removable lanyard

Built in pocket/belt clip

Dual body switches

Wide-beam floodlight

SAFETY RATING

cETLus, ATEX, IECEx and MSHA listed Intrinsically Safe Permissible for use in both above and below ground hazardous locations where explosive gases and dusts may be present

Patent 7,738,229

Bayco Products, Inc.

Permissible Nightstick 5422 Flashlight/Floodlight

MSHA

APPROVAL No. 20-A130001-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

WARNINGS:

1) MSHA approved for use with three AA Duracell Type PC1500, Energizer Type EN91, and Energizer Type L91 batteries only.
2) Replace the batteries in fresh air only and replace all batteries at the same time. Do not mix batteries from different manufacturers or of different types.
3) Energizer Lithium (Type L91) batteries are to be replaced by a qualified technician only.
4) The Model Nightstick 5422 must not be opened in areas where permissibility is required.

c ETL us
ID 4003544
INTRINSICALLY SAFE
IEC 60079 INTERNATIONAL

CLASS I DIV 1 GRPS A-D T3
CLASS II, III DIV 1 GRPS E-G T135C
CLASS I ZONE 0 AEx ia IIC T3 Ga
CLASS I ZONE 0 Ex ia IIC T3 Ga
Ex ia I Ma
Ex ia IIC T3 Ga
Intertek ITS 13 ATEX27837X
IECEx ETL 13.0026X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell AA Alkaline
CE 0359

Conforms to:
ANSI/UL 913, ANSI/UL 60079-11, ANSI/UL 60079-0
Certified to:
CAN/CSA STD C22.2 NO 157
CAN/CSA STD C22.2 No 60079-11
CAN/CSA STD C22.2 No 60079-0
CSA STD C22.2 No 25

Model	UPC 0 17398
XPP-5422G	80093 8
XPP-5422B	80094 5

Limited Lifetime Warranty • Product is warranted to be free from defects in workmanship and materials for the lifetime of the original owner. Includes the LEDs, housing, lenses, electronics and switches. Batteries, normal wear and abuse are excluded.