

## XPR-5572

### Rechargeable Intrinsically Safe Permissible Multi-Function Dual-Light™ Angle Light

**MARKET APPLICATIONS DESCRIPTION**

Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

The XPR-5572R Rechargeable Intrinsically Safe Permissible Multi-Function Dual-Light™ Angle Light is a Flashlight, a Floodlight and a Dual-Light Angle Light that is cULus and MSHA certified Intrinsically Safe Permissible. The flashlight setting offers 3 user-selectable brightness settings of 200, 100 and 60 Lumens plus a strobe feature with a 267 meter beam distance. The ultra-tight beam is perfect for cutting through smoke and lighting up objects at great distances. The floodlight setting has 3 user-selectable brightness settings of 200, 100 and a "Survival Mode" of 20 lumens that provides just enough light in an emergency situation with a run-time of 3 ½ days. The Dual-Light mode allows the user to simultaneously see objects at a distance or through the smoke, as well as see the ground in front of them as they walk or work. The 5572 is powered by a rechargeable Lithium-ion battery pack. The 5572 meets requirements of NFPA-1971-8.6 (2013).

**CASE MATERIAL**

Glass-filled Nylon Polymer Housing

**DIMENSIONS**

Length: 7.6 inches (192 mm) • Width: 3.2 inches (80 mm) • Depth: 3 in (77 mm) • Bezel Diameter: 2.8 in (70 mm)

**WEIGHT**

Weight: 13.7 oz. (388g) with rechargeable Li-ion battery pack installed

**LENS**

Unbreakable polycarbonate with scratch resistant coating

**LIGHT SOURCE**

Flashlight: CREE® LED with a 50,000 hour lifetime

**LIGHT OUTPUT**

Flashlight: 200 lumens, Floodlight: 200 lumens, Dual-Light: 200 lumens

**ON/OFF**

Dual Body Switch - Flashlight: High, Medium, Low and Floodlight: High, Medium, Survival

**RUN-TIME**

Flashlight: High: 6 hours, Medium: 11.5, Low: 22.5, Floodlight: High: 6 hours, Medium: 11.5, Survival: 30

**BATTERY**

Li-ion battery pack (included)

**FEATURES**

- cULus and MSHA certified Intrinsically Safe Permissible
- CREE LED technology – 50,000+ hours LED life
- Flashlight/Floodlight/Dual-Light™
- 3 brightness settings on the Flashlight plus a strobe
- High-efficiency deep parabolic reflector
- 3 brightness setting on the Floodlight including a 20 Lumen Survival Mode
- Glass-filled Nylon Polymer housing
- Dual body switches
- Heavy-duty stainless-steel pocket clip
- Waterproof
- Impact & chemical resistant
- Meets requirements of NFPA-1971-8.6 (2013)
- Serialized for personal identification
- Powered by rechargeable Li-ion battery pack (included)
- Can also be powered by 6 AA batteries (not included) using the AA Battery Carrier (included)

Permissible Nightstick XPR-5572 Flashlight/Floodlight

**MSHA** APPROVAL No. 20-A150005-0

TESTED FOR INTRINSIC SAFETY IN METHANE-AIR MIXTURES ONLY

WARNINGS: Do not charge in hazardous location. MSHA approved for use with Bayco Li-ion Battery Pack 5572-BATT or Primary 5570-BATT Battery Pack containing 6 AA Energizer Type EN91 or L91 batteries. Replace the Battery Pack in fresh air only. Do not mix batteries from different manufacturers or different types. Battery Pack to be replaced by a qualified technician only. The Model Nightstick 5572 must not be opened in areas where permissibility is required. Substitution of components may impair Intrinsic Safety.

---

Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS

**UL** LISTED  
E 467756  
CE 0359

UL listed for use with Bayco Li-ion Battery Pack 5572-BATT or Primary 5570-BATT Battery Pack containing 6 AA Energizer Type EN91 or E91 batteries.

CLASS I DIV I GRPS A-D T3  
CLASS II & III DIV I GRPS E-G  
CLASS I ZONE 0 Group IIC T3  
CLASS II ZONE 20 Group IIIC T3  
-20°C ≤ Tamb ≤ +70°C

**WARRANTY**

Limited Lifetime Warranty • Includes the LEDs, housing and lenses. Rechargeable batteries, chargers, switches, electronics and included accessories are warranted for a period of two years with proof of purchase. Disposable, non-rechargeable batteries are excluded from this warranty. Normal wear and failures which are caused by accidents, misuse, abuse, faulty installation and lightning damage are also excluded.

**APPROVALS**



FL1 STANDARD	DUAL-LIGHT	HIGH	MEDIUM	LOW
	200 LUMENS	200 LUMENS	100 LUMENS	60 LUMENS
	8h	6h	11h	22h
	235m	267m	199m	145m
	13836cd	22249cd	14828cd	7790cd
	2m			
	1m			

