

3 AA BATTERIES

XPP-5456G

INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

NIGHTSTICK[®]
Life Depends on Light[™]



Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**



ANSI IP-67 Dustproof / Waterproof with a 2 meter drop rating.



Adjustable ratchet tilt head made from an engineered polymer housing



Balanced weight distribution, reduces neck fatigue.

CERTIFIED



175 LUMENS

1-800-233-2155 · 1-469-326-9400 · nightstick.com

© 2021 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates.

INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

3 AA BATTERIES

ITEM NUMBER/UPC

- XPP-5456G, UPC 0 17398 80156 0

MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

CERTIFICATIONS

- cETLus, CE, ATEX, IECEx, MSHA, UKCA

CASE MATERIAL

- Engineered polymer

SPOTLIGHT LUMENS/RUNTIME

- WHITE: 100L, 18 hrs. runtime

FLOODLIGHT LUMENS/RUNTIME

- HIGH WHITE: 90L, 13.5 hrs. runtime
 - LOW WHITE: 20L, 75 hrs. runtime
 - RED: 18L, 37 hrs. runtime

DUAL-LIGHT LUMENS/RUNTIME

- 175L, 6.5 hrs. runtime

CANDELA

- 4,820

BEAM DISTANCE

- 140m

DUST/WATER RATING

- ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 3.3 in (843 mm)
 - WIDTH: 3.3 in (84 mm)
 - DEPTH: 3.5 in (89 mm)
 - WEIGHT: 9.5 oz (269 g)

BATTERY







- AA

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Headlamp
 - Elastic non-slip headband
 - Rubber hardhat strap
 - 3 AA batteries

FL 1 STANDARD	SPOT HIGH	FLOOD LOW	DUAL-LIGHT
	100 LUMENS	18 LUMENS	175 LUMENS
	18h	37h	6h 30min
	140m		
	4820cd		
			
			

Permissible Nightstick XPP-5456G Headlamp

MSHA APPROVAL No. 20-A130002-0

TESTED FOR INTRINSIC SAFETY IN METHANE AIR MIXTURES ONLY

WARNINGS: 1) MSHA approved for use with three AA Duracell Type PC1500, Energizer Type (DRI) and Energizer Type (LI) batteries only.
 2) Energizer Lithium (Type LI) batteries are to be replaced by a qualified technician only.
 3) Replace the batteries in fresh air only.
 4) Replace all batteries at the same time.
 5) Do not mix batteries from different manufacturers or of different types.
 6) The Model XPP-5456G Safety Headlamp must not be opened in areas where permeability is required.
 7) The Model XPP-5456G Safety Headlamp is approved as a mine light under 30CFR, Part 20. It is not approved as a cap lamp under 30CFR, Part 19.

ETL CLASS DIV 1 GRP A D T3 Ex ia I Ma
 CLASS II & III DIV 1 GRP B, C, D T3 C1C Ex ia I C T3 Gb
 CLASS I ZONE 0 Ex ia I C T3 Gb
 ID 4003544 Ex ia I Ex ia I Ma
 INTRINSICALLY SAFE Ex ia I C Ex ia I C T3 Gb
 SECURITY INTRINSIC Ex ia I C Ex ia I C T3 Gb

UK CA

Conforms to: ANSIL STD 913, ANSIL 60079-0, ANSIL 60079-11, ANSISA 60079-26

Certified to: CAN/CSA STD C22.2 No 157, CAN/CSA STD C22.2 No 60079-0, CAN/CSA STD C22.2 No 60079-11, CSA STD C22.2 No 25

CERTIFIED

© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates. XPP-5456G-21

