

# X-Series Intrinsically Safe Low-Profile Dual-Light™ Headlamp

Spot High Spot Low



Flood High Flood Low Dual



**200 Lumens**  
**Dual-Light™**  
**180/100 Lumens**  
**Spotlight**  
**180/100 Lumens**  
**Floodlight**



- Low-profile design
- cULus, ATEX, and IECEx listed Intrinsically Safe
- Beam distance rated at 106 meters
- Polymer housing

This X-Series Intrinsically Safe Low-Profile Dual-Light™ Headlamp is cULus, ATEX and IECEx listed Intrinsically Safe and is designed specifically to work on fire helmets and hard-hats that have a flip-up face shield. The unique low-profile shape allows the user to work without having to remove the headlamp when raising or lowering their face shield. The XPP-5460GX is manufactured from glass-filled nylon polymer and features a multi-position tilt head design. Both the spotlight and the floodlight use CREE® LED's and an advanced (TIR) Total Internal Reflection lens designed to optimize lumen output and beam pattern. Front mounted dual switches provide easy access to the spotlight for distance illumination, the floodlight for close-up illumination, and Dual-Light for maximum lighting, versatility and user safety. The XPP-5460GX includes a heavy-duty rubber head strap for use on a fire helmet or hard-hat, and is powered by 3 AAA batteries (included).

**INTRINSICALLY SAFE**



**XPP 5460GX**

# X-Series Intrinsically Safe Low-Profile Dual-Light™ Headlamp

## FEATURES

- cULus, ATEX and IECEx listed Intrinsically Safe
- CREE® LED technology – 50,000+ hours LED
- Focused high/low-brightness spotlight beam for distance illumination
- Unfocused high/low-brightness wide-beam floodlight for close-up illumination
- Dual-Light™ (spotlight and floodlight on at the same time) for maximum versatility
- Glass-filled nylon polymer housing
- (TIR) Total Internal Reflection lens designed to optimize lumen output and beam pattern
- Dual switches located on front of light
- Adjustable tilt head
- Heavy-duty rubber strap for fire helmets and hard hat applications
- Dustproof / Waterproof
- Impact & chemical resistant
- Powered by 3 AAA batteries (included)
- Limited Lifetime Warranty






## INCLUDED

- Headlamp
- 3 AAA batteries
- Heavy-duty rubber hard hat strap

<b>Model</b>	<b>UPC 0 17398</b>
XPP-5460GX	80604 6




## SPECIFICATIONS

- Lumens: high spotlight-180, low spotlight-100, high floodlight-180, low floodlight-100, dual-light-200
- Run-time: high spotlight-3.5 hrs, low spotlight-10 hrs, high floodlight-3.5 hrs, low floodlight-10 hrs, dual-light-3 hrs
- Beam distance: 106 meters
- Water / Dust rating: IP-67
- Drop rating: 2 meters
- Length: 3.54in, width: 1.58in, depth: 1.875in, weight: 5.8oz

FL1 STANDARD	DUAL-LIGHT	HIGH	LOW
	<b>200 LUMENS</b>	<b>180 LUMENS</b>	<b>100 LUMENS</b>
	<b>3h</b>	<b>3h 30 min</b>	<b>10h</b>
	<b>78m</b>	<b>106m</b>	<b>74m</b>
	<b>1528cd</b>	<b>2799cd</b>	<b>1399cd</b>
	<b>2m</b>		<b>1m</b>

## SAFETY RATING

cULus, ATEX, and IECEx listed Intrinsically Safe

<b>Bayco Products, Inc. XPP-5460</b>	
Wylie, TX 75098	
	Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS
<b>LISTED</b>	CLASS I DIV 1 GRPS A-D T4 Ex ia IIC T4 Ga
E 467756	CLASS II & III DIV 1 GRPS E-G DEMKO 17 ATEX 1824
INTRINSICALLY SAFE	CLASS I ZONE 0 GRP IIC T4 IECEx UL 17.0003
SECURITE INTRINSEQUE	CLASS II ZONE 20 IIC T135°C -20°C ≤ Tamb ≤ +40°C
	0359
	II 1 G Ex ia IIC T4 Ga 1.5V/Cell / E92 or EN92
<b>WARNINGS:</b>	
Replace batteries in a non-hazardous location.	
Use only Energizer Model E92 or EN92 batteries.	
<b>AVERTISSEMENT:</b>	
Remplacer les piles dans une zone non dangereuse.	
Utiliser uniquement les piles Energizer AAA - modèle E92 ou EN92.	